

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE

PRODUCT SUMMARY

LEDBAR CONTOUR 1617 DYNAMIC WHITE is tunable from 2200K to 5700K to provide a continuous flexible LED strip in just the right tone of light to set to the mood in dynamic architecture.


The High performance Silicone jacket material provides excellent weatherproofing, UV resistance and a wide working temperature range making it suitable for interior, exterior & underwater applications.

Single length of up to 20m can be powered from one end, minimising joins and control gear locations.


DYNAMIC WHITE




2200K-5700K




Fresh Water



Sea Water
(Salinity≤4%)



Swimming pool
(Chlorine≤5PPM)



Swimming pool
(Ozone≤0.3PPM)



Spring Water
(conditions are restricted)

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE



Silicone

PVC



5 Year
Warranty



3 Year
Warranty



Solvents
Resistant



UV
Resistant



Flame
Resistant



Salt Water
Resistant



IK10
Protection

ENVIRONMENT

Ambient Working Temperature

Silicone
12W/m -40~55°C
PVC
12W/m -20~45°C

Ambient Installation Temperature

Silicone $\geq -40^{\circ}\text{C}$ PVC $\geq 0^{\circ}\text{C}$

Max. Mounting Surface Temperature

Silicone = 85°C PVC = 60°C

Chlorine Levels

Silicone Casing is suitable for swimming pools with Chlorine $< 2\text{ppm}$. Use PVC Casing if Chlorine $> 2\text{ppm}$

COLOURS AVAILABLE





2200K-5700K

Supply Voltage


DC24V

VERTICAL BENDING



AVERAGE BEAM ANGLE (50%): 113.2°

Silicone



Bending-extreme
7072 times

Tensile-instantaneous
 $> 100\text{ kg.f}$

Twist-extreme
14441 times

PVC


Bending-extreme
5000 times

Tensile-instantaneous
52 kg.f

Twist-extreme
6131 times


Min. Bending Diameter
300mm/11.81in

Min. Cutting Length
83.3mm/3.28in
12LEDs




WARNING: Data for Laboratory Test ONLY.
For normal use ONLY bend in vertical direction.

HORIZONTAL BENDING




AVERAGE BEAM ANGLE (50%): 110.5°



Min. Bending Diameter
300mm/11.81in

Min. Cutting Length
83.3mm/3.28in
12LEDs



Silicone

Bending-extreme
6459 times

Tensile-instantaneous
 $> 100\text{ kg.f}$

Twist-extreme
7094 times

PVC

Bending-extreme
4698 times

Tensile-instantaneous
52 kg.f

Twist-extreme
9116 times

WARNING: Data for Laboratory Test ONLY.
For normal use ONLY bend in horizontal direction.

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE

EXAMPLE SPECIFICATION

71011135-2257-W-0833-C0B0

LEDBAR CONTOUR 1617 DYNAMIC WHITE IP68, White Silicone Outer Casing, Vertical Bend, 12W/m LEDs, CRI 80+ 2200K-5700K at 833mm Cut Length, Single Ended Wiring with Injection Moulded End Caps,
 END1 = IP68 Injection Moulded End Feed Cap with 0.3m Cable
 END2 = IP68 Injection Moulded Dead End Cap with NO Cable

Total Length (+ End Caps) = 843mm, Light Emitting Surface Length = 833mm (10 x 83.3mm LED Modules),
 Strip wattage = 10W (10 x 1W Module Power), Strip output = Up to 270lm.

PRODUCT CODE EXAMPLE : 7101 1 1 3 5 - 2257 - W - 0833 - C 0 B 0

CASING MATERIAL	SILICONE	PVC
CODE	1	2

BEND DIRECTION	VERTICAL BEND	HORIZONTAL BEND
CODE	1	2

STRIP POWER (W/m)	LED Module length (mm)	Module Power (W)	CODE
12	83.3	1	5

COLOUR MIX	CCT (K)	CRI	Lumen Output / Wattage (lm/m)				CODE
			12				
			SILICONE		PVC		
			Vertical	Horizontal	Vertical	Horizontal	
2200K-5700K	2200	80+	220	220	180	180	2257
	5700		270	270	180	180	

CUT LENGTH	
LED Wattage	12W
Minimum (mm)	83.3
Maximum (mm) (With power from one end)	15,000
CODE (Example with 10 Modules + End Caps)	0833

END 1 CAP	Cut No Cap	Injection Cap Dead End	Injection Cap End Feed	Injection Cap Rear Feed	Injection Cap Left Feed	Injection Cap Right Feed	BAIL Cap Dead End	BAIL Cap End Entry
CODE	A	B	C	D	E	F	G	H


END 1 CABLE	0 / 0.3m	1m	3m	5m	10m	15m	20m
CODE	0	1	3	5	10	15	20

END 2 CAP	Cut No Cap	Injection Cap Dead End	Injection Cap End Entry	Injection Cap Rear Entry	Injection Cap Left Entry	Injection Cap Right Entry	BAIL Cap Dead End	BAIL Cap End Entry
CODE	A	B	C	D	E	F	G	H


END 2 CABLE	0 / 0.3m	1m	3m	5m	10m	15m	20m
CODE	0	1	3	5	10	15	20

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE


INJECTION MOULDED IP68 END CAP - UP TO 3M DEPTH & FACTORY FITTED



BAIL-LATCH IP68 END CAP - UP TO 5M DEPTH & FIELD-ASSEMBLY



EXAMPLE OF OTHER CABLE CONNECTION OPTIONS - PLEASE ENQUIRE



7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE

ANTI-WICKING FERRULE - STANDARD ON IP68 BARS



IP68 - Above Water




IP68 - Under Water



The anti-wicking ferrule is designed to lower the risk of water ingress from the cable in case of inadequate waterproof treatment on site.

For underwater application, do not immerse anti-wicking ferrule in the water.

PLUG AND PLAY CABLE CONNECTOR - AVAILABLE ON REQUEST



POWER SUPPLIES AND DIMMERS

A comprehensive range of remote power supplies is available for full LEDBar range.

Constant Voltage: 24Vdc

Dimming options: Switch, Phase, 1-10V, DALI, DMX and Casambi

Exterior and interior versions available

[Please click here for LEDBar Power Supply sheet with full product offering](#)

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE

MOUNTING PROFILE

XXXX - Specify Length in mm





PROFILE TYPE	PART NUMBER	POSSIBLE INSTALLATION
Underwater Thickened Plastic 	71019101-XXXX Lengths Available 35/500/1000/2000	Vertical Surface Vertical Recessed Horizontal Up Surface Horizontal Up Recessed Horizontal Down Surface Horizontal Down Recessed
Underwater Flexible Anole 	710191*5-XXXX * White = 6 Black = 7 Lengths Available 55/205/475/1000	Vertical Surface Vertical Recessed Horizontal Up Surface Horizontal Up Recessed Horizontal Down Surface Horizontal Down Recessed
Rigid Aluminium 	71019111-XXXX Lengths Available 35/500/1000/2000	Horizontal Up Surface Horizontal Up Recessed
Rigid Aluminium with Flange 	71019112-XXXX Lengths Available 35/500/1000/2000	Horizontal Up Recessed
Rigid Aluminium + Serrated Rubber In 	71019121-XXXX Lengths Available 20/500/1000/2000	Vertical Surface Vertical Recessed Horizontal Up Surface Horizontal Up Recessed Horizontal Down Surface Horizontal Down Recessed
Rigid Aluminium with Flange + Serrated Rubber Insert 	71019122-XXXX Lengths Available 20/500/1000/2000	Vertical Recessed Horizontal Up Recessed Horizontal Down Recessed

Light Projects specifications are liable to be changed without notice.

7101xx3x LEDBAR CONTOUR 1617 DYNAMIC WHITE

MOUNTING PROFILE

XXXX - Specify Length in mm

PROFILE TYPE	PART NUMBER	POSSIBLE INSTALLATION					
Flexible Aluminium with Serrated Rubber Insert Horizontal Bending 	71019131-XXXX Lengths Available 500/1000						
Flexible Aluminium Self-clinching Vertical Bending 	71019133-XXXX Lengths Available 500/1000						
Rigid Aluminium Self-clinching 	71019141-XXXX Lengths Available 20/500/1000/2000						

Light Projects specifications are liable to be changed without notice.